

NYX

IPB4-28F

4MP PoE IP Bullet

Features

- 4MP (2592x1520) H.265 full real time encoding
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- 3D DNR, digital WDR
- ROI encoding
- Support CVBS video output and one-way audio
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Triple Stream



ONVIF

Specifications

Image Sensor	1/3" CMOS
Resolution	4MP(2592x1520), 2MP, 720P, D1, CIF
Min. Illumination	0.05 lux @F1.2, AGC on; 0 lux with IR
Lens	3.6mm @F1.6, Angle of View 72°
Day & Night	ICR Filter
Video Format	H.265 / H.264 / MJPEG
Main Stream	60Hz: 4MP/3MP/2MP/720P(1~30fps) 50Hz: 4MP/3MP/2MP/720P(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Video Analytics	Intrusion, Missing/Abandoned Object, Trip-wire
Audio	Mic input x1
Video Out	CVBS
Smart Alarm	Motion Alarm
IR Distance	20~30m
Remote	IE Browser, CMS Software up to 10 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / PoE
Power Usage	<2.5W (<6W with IR on)
Operating Env.	-20°~ 50°C, 10%~90% Humidity
Dimensions	Ø 87 x 219mm
Weight	609g

Intelligence Analytics

Get **FAST** search results by configuring in-built **image analytic algorithms**.

Supports Tripwire, Abandoned Object, Missing Object, Video Exception & Intrusion



H.265 HEVC

More **efficient** video encoding allows for **longer** recording time without sacrificing **image quality**



4MP Sensor



0 Lux Min. Illumination



Digital WDR



Motion Detection



True Day&Night



AWB



Sync



AGC




PoE



IP66 Rating

Mounting Accessories

JB-EB



WM-EB



WM-EX



PARADISE SECURITY
AUSTRALIA PTY LTD

P: (07) 5549 2911
www.paradisecurity.com.au

