

MYX

IPD2-28FS

STARLIGHT series

Features

The new **STARLIGHT** series enhances night vision and greatly reduces image noise ensuring sharp video at night.

- 2MP (1920×1080) H.264 @ 25/30fps
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- 3D DNR, digital WDR
- ROI encoding
- Support CVBS video output and one-way audio
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Triple Stream



ENHANCED LOW NOISE NIGHT VISION

Specifications

Image Sensor	1/2.7" CMOS
Resolution	2MP(1920x1080), 720P(1280x720), D1, CIF
Min. Illumination	0.01 lux @F1.2, AGC on; 0 lux with IR
Lens	3.6mm @F1.6, Angle of View 77°
Day & Night	ICR Filter
Video Format	H.264 / MJPEG
Main Stream	60Hz: 1080P(1~30fps) / 720P(1~30fps) 50Hz: 1080P(1~25fps) / 720P(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Audio	Mic input x1
Video Out	CVBS
Smart Alarm	Motion Alarm
IR Distance	10~20m
Remote	IE Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / PoE
Power Usage	<3.5W (<5W with IR on)
Operating Env.	-20°~ 50°C, 10%~90% Humidity
Dimensions	Ø 87 x 108mm
Weight	427g



Mounting Accessories



STARLIGHT

